




Lamp Type: G64T5VHCA/2S07/CB-0J6
 Aquafine P/N 18953

Spec Number:
 2788

Engineering Specification Sheet

Lamp Diagram:



Lamp Characteristics

(A) Base Face:	1567 mm	+0.76 / -3mm		
(B) ARC:	1473mm		Operating Current	780mA
(C) Bulb Diameter	15		Lamp Voltage	170V
(X)			Lamp Wattage	130W
Glass Type:	VH (Ozone)	Coating:	A11-QC-001	
If Spliced:	L	mm	VH	mm
	(Y)			

UV Output - Certified to be true. Kenneth A. Eil, President

Output UVC Watts	Output μ /cm ² @ 1 Meter	Rated Life (hrs)	% Output @EOL	Output Notes Field	Ballast Used for Measurements
54	395	12000	80.00%		LCG800MV

First Light
 212 Ideal Way
 Poultney, VT 05764 USA
 Phone-(802) 287-4195 Fax-(802) 287-4489
 www.firstlightusa.com
 email: sales@firstlightusa.com

*UV Output is based on lamps measured after 100 hours of operation under lab conditions. These values are subject to wide variations under application/field conditions.
 UV Output is measured at 254 nm
 **Rated Life is for reference purposes only and is based on a group of lamps operating under lab conditions. Actual life depends on the operating conditions of the lamp.

12/22/2015
 11:50:01 AM

This data includes matters which are trade secrets of First Light Technologies, Inc., or Proprietary or Confidential to First Light Technologies, Inc. and shall not be reproduced or disclosed in whole or part, or used in any manner except in connection with First Light Technologies, Inc. business, without the written permission of First Light Technologies, Inc.